



CONTROL BEARINGS

Consolidated Bearings offers a full line of Control Bearings. Control Bearings are available in **light**, **medium** and **heavy-duty** types. Control Bearings, with their precision manufacture and durable design, are used in a variety of applications that require a high load capacity and slow rotation. Being compact, corrosion resistant, Teflon sealed, and pre-lubricated with grease, these bearings can be used in what could be considered harsh environments. Normal operating temperatures for Control Bearings range from -65°F to +250°F.

PRODUCT APPLICATION

Consolidated's line of Control Bearings are not cadmium plated and are intended for industrial applications only such as medical devices, robotics, air frame control and materials handling systems.

HIGHLIGHTS

Compact
Corrosion resistant
Teflon sealed
Pre-lubricated with grease

GENERAL CLASSIFICATION

KP-3 ALX	KP-8 AX	KP-5 X
KP-3 AX	KP-10 AX	KP-6 X
KP-4 AX	KP-3 LX	KP-8 X
KP-5 AX	KP-3 X	KP-10 X
KP-6 AX	KP-4 X	



SERVICES



SAME OR NEXT-DAY SHIPPING

98% order fill rate. All orders are shipped the same or next day. We can service most of our customers in 1-2 days via standard shipping.



WILL CALL

Nine strategically located warehouses across the country. Orders can be made available for will call and customer pickups.



AFTER HOURS SERVICES

Available 24/7 to handle all of your emergency requirements. For immediate assistance, please call your local toll free number.



CUSTOMER SERVICE

Available by phone, fax, email or online and answered directly by an experienced and qualified customer service representative.

LOCATIONS

Need a bearing immediately? We offer after-hours emergency services at all of our nine locations. For after-hours support, please call your district's toll-free number and follow the prompts.

